AGRI MAGAZINE
(International E-Magazine for Agricultural Articles)
Volume: 02, Issue: 12 (December, 2025)
Available online at http://www.agrimagazine.in
©Agri Magazine, ISSN: 3048-8656

Application of Biofloc Technology in Sustainable Aquaculture Systems

*Tanya
Ph.D. Scholar, Department of Zoology, Keral Verma Subharti College of Science, Swami Vivekanand Subharti University, Meerut-250005, UP, India
*Corresponding Author's email: tanyachaudhary30062002@gmail.com

The intensification of aquaculture to meet global seafood demand has raised concerns over water pollution, disease outbreaks, and resource inefficiency. Biofloc technology (BFT) is an innovative, eco-friendly approach that enhances water quality, recycles nutrients, and promotes sustainable production. By manipulating the carbon-to-nitrogen (C:N) ratio, BFT stimulates microbial growth that assimilates nitrogenous wastes into biomass, which acts as a supplemental feed for cultured species. This review examines the principles, applications, environmental and economic benefits, challenges, and future prospects of biofloc technology in aquaculture. Case studies, operational data, and comparative analyses highlight its potential to increase productivity while minimizing environmental impact.

Introduction

Aquaculture has emerged as a critical sector in global food security, providing high-quality protein and essential nutrients. However, conventional aquaculture systems are often associated with environmental degradation due to effluent discharge, high feed input, and water exchange. These factors contribute to eutrophication, disease outbreaks, and resource inefficiency. Therefore, innovative solutions are required to make aquaculture more sustainable. Biofloc technology (BFT) represents a paradigm shift in aquaculture management by turning waste into a resource. By promoting beneficial microbial growth, BFT not only improves water quality but also supplements feed and enhances animal health. Over the last two decades, biofloc systems have been widely adopted in shrimp and tilapia culture worldwide, demonstrating improved survival rates, feed conversion efficiency, and overall productivity.

Scientific Basis of Biofloc Technology

Biofloc technology relies on microbial nitrogen assimilation in response to controlled C:N ratios. In conventional aquaculture, ammonia accumulation from feed and excreta leads to toxicity. By adding carbon-rich substrates such as molasses, starch, or rice bran, heterotrophic bacteria proliferate and convert ammonia into microbial biomass. These microbial aggregates, or bioflocs, consist of bacteria, algae, fungi, protozoa, and organic matter bound by extracellular polymeric substances (EPS). Bioflocs remain suspended through aeration and serve as a natural feed source. This system minimizes the need for water exchange, reduces nutrient discharge, and enhances biosecurity. Maintaining an optimal C:N ratio (usually 15–20:1) is critical to maximize microbial growth while preventing excessive biofloc accumulation.

Table 1: Typical C:N Ratio and Carbon Sources in Biofloc Systems

Carbon Source	Recommended C:N Ratio	Application Notes
Molasses	15–20:1	Rapid microbial growth, cost-effective
Wheat flour	15–20:1	Slower assimilation, stabilizes floc

Starch	15–20:1	Low-cost, supports heterotrophic bacteria
Sugarcane juice	15–18:1	Rapid carbon availability, seasonal use

Applications of Biofloc Technology in Aquaculture Systems

Water Quality Regulation and Nutrient Recycling

Biofloc systems maintain water quality by converting toxic nitrogenous compounds into microbial biomass. Ammonia, nitrite, and nitrate levels are effectively regulated through heterotrophic assimilation and microbial nitrification. Reduced water exchange not only minimizes pathogen introduction but also conserves water, making BFT suitable for areas with limited water availability. Biofloc systems also act as a nutrient reservoir. The microbial community transforms organic waste into digestible protein, reducing the need for external feed inputs. Continuous aeration ensures flocs remain in suspension, maintaining optimal water quality and promoting system stability.

Table 2: Water Quality Parameters in a Typical Biofloc Tilapia System

Parameter	Ideal Range for BFT	Observed Effect on Fish Health
Ammonia (NH_3) mg/L	<0.5	Prevents gill damage, improves survival
Nitrite (NO_2^-) mg/L	<1.0	Reduces stress and mortality
Dissolved Oxygen (mg/L)	4–6	Supports microbial activity and fish respiration
pH	7–8	Maintains microbial balance
Temperature (°C)	25–30	Optimal for tilapia and shrimp growth

Biofloc as a Functional Feed Resource

Bioflocs provide a continuous, protein-rich feed containing essential amino acids, fatty acids, vitamins, and minerals. Studies indicate that consuming bioflocs enhances growth rates, feed conversion ratios (FCR), and immunity in cultured species. In shrimp and tilapia culture, bioflocs can provide 20–30% of daily protein requirements, significantly reducing feed costs. The nutritional composition of bioflocs depends on the carbon source, microbial species, and system management. Maintaining appropriate floc size (50–100 µm) ensures optimal ingestion and digestion by cultured species. Additionally, bioflocs stimulate digestive enzyme production, promoting nutrient absorption.

Table 3: Nutritional Composition of Bioflocs

Component	Typical Concentration (%)	Notes
Crude Protein	25–40	Depends on microbial community
Lipids	5–12	Provides essential fatty acids
Carbohydrates	10–20	Energy source for fish/shrimp
Minerals	5–8	Calcium, phosphorus, trace elements
Vitamins	Variable	B-complex, A, D, E depending on microalgae presence

Disease Management and Biosecurity

Biofloc systems enhance disease resistance by establishing a stable microbial community that suppresses pathogens via competitive exclusion. Beneficial bacteria such as *Bacillus* spp. dominate the system and inhibit opportunistic pathogens like *Vibrio* spp. Additionally, ingestion of bioflocs stimulates innate immunity, increasing survival under stress conditions. The reduced water exchange in BFT also limits pathogen introduction from external sources. Studies show lower mortality rates and reduced antibiotic use in biofloc-based shrimp farms compared to conventional systems. This contributes to safer, more sustainable aquaculture practices.

Role of Biofloc Technology in Sustainable Aquaculture

Environmental Sustainability

By recycling nutrients within the system, BFT minimizes effluent discharge and reduces eutrophication risks. Reduced water usage conserves freshwater resources, addressing

environmental and regulatory concerns. Additionally, bioflocs sequester nitrogen in microbial biomass, preventing toxic accumulation and maintaining ecosystem balance.

Economic and Operational Sustainability

Biofloc systems allow for intensive culture in limited areas, improving profitability per unit area. Reduced feed and water costs, along with higher survival rates, enhance overall farm economics. Shrimp and tilapia cultured in biofloc systems demonstrate up to 20–30% higher growth rates compared to conventional systems under similar stocking densities.

Table 4: Growth Performance Comparison Between Biofloc and Conventional Systems

Species	System Type	Growth Rate (g/week)	FCR	Survival Rate (%)
Tilapia	BFT	4.5	1.2	90
Tilapia	Conventional	3.2	1.6	80
Shrimp (*L. vannamei*)	BFT	2.8	1.3	88
Shrimp (*L. vannamei*)	Conventional	2.0	1.8	75

Social and Livelihood Benefits

Biofloc technology supports small-scale and urban aquaculture by enabling high productivity in limited spaces. Reduced chemical use and enhanced biosecurity improve consumer confidence in aquaculture products. Additionally, BFT adoption creates livelihood opportunities in peri-urban and rural areas while promoting eco-friendly practices.

Challenges and Limitations

Despite its advantages, biofloc systems require technical expertise. Maintaining optimal C:N ratios, aeration, and floc density is critical. High energy demand for aeration and mixing increases operational costs, which can be a barrier for small-scale farmers. Excessive floc accumulation may lead to oxygen depletion and poor water quality if not managed properly. Continuous monitoring and system adjustments are therefore essential for long-term success.

Integration with Advanced Aquaculture Systems

Biofloc technology can be combined with recirculating aquaculture systems (RAS) and aquaponics to maximize resource efficiency. Integrating BFT with renewable energy sources, probiotics, or feed additives can further improve productivity, sustainability, and economic viability.

Future Prospects and Research Needs

Future research should focus on optimizing microbial community management, cost-effective carbon sources, and energy-efficient aeration systems. Advanced monitoring, automation, and real-time water quality sensors can improve system control. Species-specific biofloc formulations, tailored to growth and nutritional requirements, may further enhance production efficiency.

Conclusion

Biofloc technology represents a sustainable, eco-friendly, and economically viable solution for intensive aquaculture systems. By converting waste into a resource, improving water quality, supplementing feed, and enhancing disease resistance, BFT addresses key challenges of modern aquaculture. With proper management, training, and technological innovation, biofloc systems can significantly contribute to environmentally responsible and high-yield aquaculture production.

References

1. Avnimelech, Y. (2009). *Biofloc Technology: A Practical Guide Book*. World Aquaculture Society.
2. Crab, R., Defoirdt, T., Bossier, P., & Verstraete, W. (2012). Biofloc technology in aquaculture: Beneficial effects and future challenges. *Aquaculture*, 356–357, 351–356.
3. Emerenciano, M., et al. (2017). Biofloc technology in shrimp culture. *Reviews in Aquaculture*, 9, 1–19.