AGRI MAGAZINE
(International E-Magazine for Agricultural Articles)
Volume: 03, Issue: 11 (November, 2026)
Available online at http://www.agrimagazine.in
©Agri Magazine, ISSN: 3048-8656

Light-Powered Air Purification: How A White Powder is Transforming Buildings into Pollution Fighters

*R Vishalini
M.Sc. Scholar, Department of Environmental Science, TNAU, Coimbatore, India
*Corresponding Author's email: vishalinirajavel.2331@gmail.com

Photocatalytic air purification is an emerging technology that uses light-activated materials, particularly titanium dioxide (TiO_2), to reduce air pollution. When exposed to sufficient light, TiO_2 generates reactive species that transform pollutants such as nitrogen oxides (NO_x), volatile organic compounds (VOCs) and sulphur dioxide into less harmful products. Incorporating TiO_2 into cement, tiles, glass, paints, and road surfaces can give ordinary building materials pollution-removal properties. Although laboratory studies and real-world applications have shown promising results, challenges remain, including limited visible-light activity, catalyst deactivation, durability, and maintenance costs. Developing efficient, durable and sunlight-responsive photocatalytic materials could support cleaner and more sustainable urban environments.

Introduction

Traffic, industrial activity and fuel combustion release a mixture of air pollutants, including nitrogen oxides (NO_x), sulphur oxides (SO_x), volatile organic compounds (VOCs) and fine particles. Exposure to polluted air is associated with respiratory and cardiovascular illness, while pollutants can also affect vegetation, soil and water. Sulphur oxides contribute to acid deposition, which can damage buildings, alter soil chemistry and harm crops. Air quality is therefore not only an urban concern; it also matters to agriculture and environmental management. [1] This is the idea behind photocatalytic construction materials. Titanium dioxide can be incorporated into cement, tiles, glass, paints and road surfaces. When light activates the material, reactions take place at the surface and can transform certain airborne contaminants. The approach does not replace emission controls or conventional air-quality measures, but it offers a way to add a pollution-removal function to infrastructure that is already in place. A review published in 2009 described the development and growing use of photocatalytic construction materials, including early uptake in Japan.[2]

The science: sunlight, a white powder and invisible cleaners

Titanium dioxide is a semiconductor. When light of sufficient energy (above 3.2 electron-volts for its common anatase form) strikes it, an electron is knocked loose and leaves behind a positively charged "hole".[3] These electron–hole pairs react with oxygen and water in the air and produce highly reactive molecules, mainly hydroxyl radicals and superoxide ions.[1,3] Think of it as a solar panel that, instead of making electricity, makes tiny cleaning agents. These molecules attack pollutants on contact. Organic compounds such as formaldehyde are broken down finally into carbon dioxide and water, nitrogen oxides are converted into nitrate, and sulphur dioxide into sulphate.[1] The same reactive molecules can also rupture bacterial cell membranes and damage the genetic material of bacteria and viruses, which is why these surfaces are also being studied for disinfection.[1]

Why light-powered cleaning is attractive

Conventional air-treatment methods consume energy and can create secondary pollution of their own. Photocatalysis, in contrast, uses little energy, relies on a catalyst that is not used up in the reaction and has low toxicity.[1] Titanium dioxide is also chemically stable, inexpensive and compatible with ordinary building materials such as cement, so it can be added without changing their original properties.[1] Because the cleaning happens on surfaces that already exist, no extra land, ducts or fans are needed. This makes the approach especially attractive for dense cities, where space is limited, and traffic is the main source of nitrogen oxides.



Figure 1. Schematic illustration of the TiO_2 photocatalytic mechanism, showing light absorption, electron–hole pair generation, reactive oxygen species formation, and pollutant transformation.

From powder to pavement

TiO_2 can be produced through different methods, including sol–gel processing, hydrothermal synthesis, spray-drying, anodic oxidation and microwave-assisted techniques. Each method offers different trade-offs in cost, particle properties and process control. [1]The resulting material may be mixed into cement-based products or applied as a surface coating to tiles, paving blocks, glass and road materials. In one study, a cement paste containing 5% TiO_2 showed the strongest nitrogen-oxide removal among the formulations tested. [4] Laboratory investigations under ultraviolet illumination have reported NO_x removal in the approximate range of 40–72% for some cement-based samples, while a separate study reported formaldehyde removal of up to 65%. The type of cement also matters: white-cement mixtures have shown greater nitric-oxide removal than some ordinary Portland cement mixtures. [5]

Making it work in ordinary sunlight

Because the main weakness of titanium dioxide is that it responds mainly to ultraviolet light, only a part of what the sun delivers, researchers have tried several fixes. Its tiny particles also clump together, and the freed electrons and holes often recombine before they can do any cleaning.[1] Anchoring the particles on silica, a common building ingredient, reduces clumping and improves the capture of pollutants.[6] Carbon nanotubes and graphene help separate the electrons and holes.[1] Adding metals such as iron allows the material to absorb visible light,[7] and doping with nitrogen narrows the energy gap further. An asphalt road surface treated with nitrogen-doped titanium dioxide reduced vehicle emissions under visible light better than one treated with plain titanium dioxide.[8] Combining two dopants, such as iron and nitrogen, has given even better results in laboratory studies.[1]

Out in the real world

Several projects have moved beyond the laboratory. The Jubilee Church in Rome reportedly has a titanium dioxide facade that breaks down nitrogen oxides and volatile organic compounds while keeping its white appearance. At the north toll station of the Nanjing Yangtze River Bridge in China, researchers applied a nano-titanium dioxide material over about 6000 m², and monitoring over a few months reportedly showed nitrogen oxide removal above 80%.[1] Similar applications are reported from Germany, the Netherlands and other parts of China.

The reality check

The technology is promising, but experts caution that it is not yet a complete answer. Most laboratory results come from ultraviolet light, and performance in real sunshine and weather is still unsatisfactory.[1] Dust and reaction by-products can build up on surfaces and "poison" the catalyst, and nobody is sure how long the coatings will last.[1] The photocatalyst may even attack the binder or surface it sits on, weakening the material and shortening its life.[9] Little is known about the by-products formed on real buildings, or whether they are harmless. Most of these materials also react with many different compounds, which wastes some of their activity. Demonstration projects point to high installation and maintenance costs and weaker performance in heavy traffic and shaded spots.[1] Standard test methods and simulation tools are also still missing.

Where research is heading

Researchers largely agree on what comes next. New catalysts need to remove pollutants efficiently in natural sunlight, create little or no harmful by-products, and lengthen rather than shorten the life of the building material.[1] Smarter surface design can also improve real-world results by considering where the material sits on a building, how much light and air reach it, and how well it suits the structure.[1] Shared evaluation criteria and simulation tools are needed too, so that results from different laboratories and cities can be compared fairly. Finally, long-term field monitoring should show how coatings age, how often they need renewing and what ultimately becomes of the nitrate and sulphate they produce.

Conclusion

Photocatalytic building materials show that the surfaces we already build can be made to work for cleaner air using nothing but light. The science is well understood, and laboratory and field results are encouraging, particularly for low concentrations of nitrogen oxides. However, wide adoption depends on catalysts that work efficiently in sunlight, last for years, leave no harmful by-products and remain affordable. Whether similar surfaces could one day protect farm buildings, greenhouses and rural roads remains an open and interesting question for agricultural and environmental scientists.

References

1. Wei Y, Meng H, Wu Q, Bai X, Zhang Y. 2023. TiO2-based photocatalytic building material for air purification in sustainable and low-carbon cities: A review. *Catalysts* 13(12): 1466.
2. Chen J, Poon C-S. 2009. Photocatalytic construction and building materials: From fundamentals to applications. *Build. Environ*. 44(9): 1899–1906.
3. Schneider J, Matsuoka M, Takeuchi M, Zhang J, Horiuchi Y, Anpo M et al. 2014. Understanding TiO2 photocatalysis: Mechanisms and materials. *Chem. Rev*. 114(19): 9919–9986.
4. Cárdenas C, Tobón JI, García C, Vila J. 2012. Functionalized building materials: Photocatalytic abatement of NOx by cement pastes blended with TiO2 nanoparticles. *Constr. Build. Mater*. 36: 820–825.
5. Guo M-Z, Poon CS. 2018. Superior photocatalytic NOx removal of cementitious materials prepared with white cement over ordinary Portland cement and the underlying mechanisms. *Cem. Concr. Compos*. 90: 42–49.

6. Ghedini E, Menegazzo F, Manzoli M, Di Michele A, Puglia D, Signoretto M. 2019. Multifunctional and environmentally friendly TiO2-SiO2 mesoporous materials for sustainable green buildings. *Molecules* 24(23): 4226.
7. Liu M, Qiu X, Miyauchi M, Hashimoto K. 2013. Energy-level matching of Fe (III) ions grafted at the surface and doped in the bulk for efficient visible-light photocatalysts. *J. Am. Chem. Soc.* 135(27): 10064–10072.
8. Chen M, Baglee D, Chu JW, Du D, Guo X. 2017. Photocatalytic oxidation of NOx under visible light on asphalt-pavement surface. *J. Mater. Civ. Eng.* 29(8): 04017133.
9. Chew MYL, Conejos S, Law JSL. 2017. Green maintainability design criteria for nanostructured titanium dioxide (TiO2) façade coatings. *Int. J. Build. Pathol. Adapt. 35(2): 139–158.*